

## OUTPUT CHARACTERISTICS

MODEL	WATTAGE	OUTPUT					
		+5V	+12V	+3.3V	-5V	-12V	+5VSB
P2P-5650P	650W	30A	50A	25A	X	0.8A	3.0A
P2P-5700P	700W	30A	50A	25A	X	0.8A	3.0A
REGULATION LOAD		±5%	±5%	±5%	X	±10%	±5%
RIPPLE AND NOISE		60mV	120mV	60mV	X	120mV	60mV

REMARKS : +5V AND +3.3V TOTAL OUTPUT MAX : 170W



## P2P-5650P P2P-5700P

### INPUT CHARACTERISTICS:

VOLTAGE :

90~264VAC FULL RANGE

FREQUENCY :

47 ~ 63 HZ

INPUT CURRENT :

WATTAGE	115V	230V
650W	11A	5A
700W	11A	5A

INRUSH CURRENT:

35/70 AMPS @ 115/230VAC

POWER FACTOR CORRECTION :

PFC CAN REACH THE TARGET OF 95% AT 115/230VAC, FULL LOAD

EMI :

IEC61000-3-2, FCC, CISPR 22(EN 55022)

EMS :

EN 61000-4-2 ESD, EN61000-4-4 EFT, EN61000-4-5 SURGE

SAFETY :

UL&CUL, TUV, CCC, GOST

SPECIFICATION:

TEMPERATURE RANGE : OPERATING 0°C ~50°C , STORAGE -20°C ~80°C

HOLD UP TIME : 16 ms MINIMUM AT FULL LOAD UNDER 90V INPUT VOLTAGE

EFFICIENCY : 80~84% TYPICAL @ FULL LOAD

POWER GOOD SIGNAL : ON DELAY 100 ms TO 500 ms, OFF DELAY 1 ms

OUTPUT PROTECTION : OPP / OVP / OCP / SCP

DIMENSION : 280 (D) x 100 (W) x 82.5 (H) mm

THE POWER-SUPPLY IS FOR CHASSIS-ASSEMBLY ONLY AND IS NOT ALLOWED TO BE OPERATED AS STAND-ALONE COMPONENT. FINAL ASSEMBLY HAS TO COMPLY WITH CORRESPONDING EMC- AND SAFETY-REGULATIONS

